RS 12-42 GEN•4







RS 12-42 GEN:4 Created on January 16, 2023 at 3:04:48 p.m. UTC

			i January 10, 2023 at 3.04.48 β.m. 01
Capacities		Metric	Imperial
Max. capacity		5443.10 kg	12000 lb
Max. lifting height		12.90 m	42 ft 4 in
Max. outreach		8.51 m	27 ft 11 in
Weight and dimensions			
Overall length to carriage	l11	5.87 m	19 ft 3 in
Overall length (with forks)	l1	5.90 m	19 ft 4 in
Overall width	b1	2.51 m	8 ft 3 in
Overall height	h17	2.41 m	7 ft 11 in
Wheelbase	У	3.15 m	10 ft 4 in
Ground clearance	m4	457.20 mm	18 in
Overall cab width	b4	838 mm	33 in
Tilt-up angle	a4	12 °	12 °
Tilt-down angle	a5	112 °	112 °
External turning radius	Wa3	4.24 m	13 ft 11 in
Unladen weight (with forks)		11431 kg	25201 lb
Overall weight		11430.53 kg	25200 lb
Standard tyres		14 x 24	14 x 24
Frame levelling longitudinal +/-		10 °	10 °
Frame levelling corrector	a9	10 °	10 °
Engine			
Engine brand		Deutz	Deutz
Engine norm		Tier 4 final	Tier 4 final
Engine model		TCD 3.6 L4	TCD 3.6 L4
Number of cylinders / Capacity of cylinders		4 - 3.80 cm ³	4 - 0.23 in ³
I.C. Engine power rating - Power (kW)		120 Hp / 89 kW	120 Hp / 89 kW
Max. torque / Engine rotation		480 Nm @ 1600 rpm	354 ft/lbs @ 1600 rpm
Transmission			
Transmission type		Torque converter with powershift	Torque converter with powershift
Number of gears (forward / reverse)		4/3	4/3
Max. travel speed		32.30 km/h	20 mi/h
Parking brake		SAHR	SAHR
Service brake		Wet disc brakes	Wet disc brakes
Axle Manufacturer		Dana	Dana
Hydraulics			
Hydraulic pump type		Gear pump	Gear pump
Hydraulic flow / Pressure		157.09 l/min / 207 bar	41 US gpm / 3002 PSI
Tank capacities			
Engine oil		14.70 l	4 US gal
Hydraulic oil		170 l	45 US gal
Fuel tank		177.91 [47 US gal
DEF tank capacity		19 [5 US gal
Miscellaneous			3**
Steering wheels (front / rear)		2/2	2 / 2
Drive wheels (front / rear)		2/2	2/2
Safety cab homologation		ROPS/FOPS	ROPS/FOPS
Controls		Single joystick with FNR	Single joystick with FNR

RS 12-42 GEN:4 - Load chart

Machine on tyres with forks Imperial





This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend