Technical sheet :








Capacities		Metric
Operating Capacity At 50% Tipping Load		1247 kg
Rated Operating Capacity with Optional Counterweight		1327 kg
perating Weight		3774 kg
Jnladen weight		3774 kg 3426 kg
Fipping capacity		2495 kg
Weight and dimensions		2493 Kỹ
Dperating Weight - Approximate		3774 kg
Iverall Operating Height - Fully Raised	h27	4252 mm
leight to Hinge Pin – Fully Raised		4232 mm
Diverall Height to Top of ROPS	h28 h17	2058 mm
		2058 mm
Dump angle at full height	a5	
Nump height	h29	2489 mm
Overall length with bucket	116	3810 mm
Dump reach - Full height	гб	830 mm
tollback Angle at Full Height	a4	92 °
Seat to ground height	h30	978 mm
Overall width less bucket	b1	1712 mm
Ground clearance	m4	216 mm
Overall length - Less Bucket	12	3023 mm
Clearance Radius - Front with Bucket	b18	2289 mm
Clearance Circle - Front without Bucket	b19	1410 mm
Clearance Circle - Rear	wa1	1829 mm
Performances		
Travel Speed with Two-Speed Option - Maximum		17.50 km/h
Travel speed (unladen)		11.40 km/h
Wheels		
Transmission type		Hydrostatic
Ingine		
Engine brand		Yanmar
Engine model		4TNV98CT-XNGL
Engine norm		Stage V
Gross Power (kW)		53.70 kW
Net Power (kW)		52.70 kW
Max. torque / Engine rotation		294 Nm / 1800 rpm
Number of cylinders		4
Engine cooling system		Water
Battery		12 V
Alternator - Ampere		100 A
Starter (kW)		3 kW
lydraulics		
Standard flow - Auxiliary hydraulics		98.40 l/min
Auxiliary Hydraulic Pressure		239.59 bar
ligh-Flow Auxiliary Hydraulics – Option		126 l/min
ligh-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar
Fank capacities		
Fuel tank		106 l
Reservoir Capacity Hydraulics		22.70
Displacement		3.30
Coolant system capacity		18

2750V - Dimensional drawing









Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes