Technical sheet:

## 3300 V NXT:2






	3300 V NXT:2 Created	on March 17, 2025 at 0.02.27 p.m. t
Capacities		Metric
Rated Operating Capacity		1497 kg
Jnladen weight		4123 kg
Weight and dimensions		
Overall Operating Height - Fully Raised	h27	4369 mm
leight to Hinge Pin – Fully Raised	h28	3332 mm
Overall Height to Top of ROPS	h17	2083 mm
lump angle at full height	a5	42 °
Dump height	h29	2502 mm
verall length with bucket	l16	3874 mm
ump reach - Full height	r6	813 mm
collback at ground	a13	29 °
eat to ground height	h30	1041 mm
/heelbase	у	1257 mm
Iverall width less bucket	b1	1829 mm
ucket Width	e1	1880 mm
round clearance	m4	229 mm
Overall length - Less Bucket	12	3023 mm
eparture angle	a2	25 °
Plearance Radius - Front with Bucket	b18	2400 mm
Clearance Circle - Front without Bucket	b19	1422 mm
Clearance Circle - Rear	wa1	1765 mm
Performances		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
ravel Speed with Two-Speed Option - Maximum		19.60 km/h
ravel speed (unladen)		13 km/h
Vheels		10 km/m
Standard tyres		14x1750 HD
ngine		1441700110
ngine brand		Yanmar
ingine model		4TNV98CT-NMS
ross Power (kW)		53.70 kW
let Power (kW)		52.70 kW
Max. torque / Engine rotation		294 Nm / 2500 rpm
attery		12 V
Alternator		95 kW
tarter (kW)		3 kW
lydraulics		3 RW
Standard flow - Auxiliary hydraulics		89.10 l/min
Luxiliary Hydraulic Pressure		237.90 bar
ligh-Flow Auxiliary Hydraulics – Option		132 l/min
ligh-Flow Auxiliary Hydraulics Pressure – Option		220.60 bar
ank capacities		220.00 bai
uel tank		92.70
uer tarik Jeservoir Capacity Hydraulics		92.701 40 l
		3.30
Visplacement		3.30 1
loise and vibration		101 10
invironmental noise (LwA)		101 dB
loise at driving position (LpA)		85 dB
Whole-Body Vibration (ISO 2631-1)		0.79 m/s <sup>2</sup>

## 3300 V NXT:2 - Dimensional drawing







## **Equipment**

_	
Integral Access Plate (removable)	Standard
Lifting function	
All-Tach® Attachment Mounting System	Standard
Auxiliary Hydraulics	Standard
High-Flow Auxiliary Hydraulics	Optional
Power-A-Tach® Attachment Mounting System	Optional
Lighting	
Work Lights - Front and Rear	Standard
Motorization/Power	
Engine Auto-Shutdown System	Standard
Engine Block Heater	Optional
Turbo-Charged Engine	Standard
Two-Speed Drive	Standard
Operator station	
Adjustable Arm Rests / Control Towers 1	Standard
Air conditioning with manual adjustment	Optional
Air suspension seat	Optional
Cab Enclosure	Optional
Dual-Hand Controls	Optional
Foot and Hand Throttles 2	Standard
Gehl T-Bar Controls	Optional
Hand/Foot Controls	Optional
Heating	Optional
High-Back Adjustable Seat	Standard
Horn	Standard
Joystick controls	Optional
ROPS/FOPS Level II Overhead Guard	Standard
Sound Reduction Material	Standard
Suspension Seat - Mechanical	Optional
Other options	opuona.
Hydrostatic Drive - Servo	Standard
Selectable Self-Leveling Hydraulic Lift Action 4	Optional
Secondary functions	o puona.
Counterweight	Standard
Full Instrumentation	Standard
Hydraglide™ Ride Control 3	Standard
Security	
Anti-Vandalism Protection	Standard
Back-Up Alarm	Optional
Brake Control (Auto / Manual)	Standard
Hydraloc™ Safety System	Standard
Lift Arm Support Device	Standard
Operator Restraint Bar	Standard





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes